



# Series 2005

*1-leave and 2-leaves door  
with middle band*

The aluminium hinged door with or without middle band Series 2005 has been realized for fitting on external and/or internal walls (mainly of small thickness) of new, existing and/or temporary structures. This typology represents a door, which combines lightness and strength. It can be realized with many adjustable profiles, in order to satisfy the most of various needs.



Air permeability  
according EN 12207

**Class 1**

Water Tightness  
according to EN 12208

**Class 8A**

Wind Resistance  
according to EN 12210

**Class C4**

Fire reaction  
In conformity to D.M.14/01/1985

**Class 0**



## DATASHEET

Depth of frame: 44 mm.

Sealing system with gasket in COECOPRENE on panel and frame.

Optional insertion of glass panels of a thickness ranging between 4 mm and 23 mm (single or stratified pane, insulating glazing); optional application of external aluminium anti-intrusion bars and/or an internal Venetian blind.

Profiles in extruded aluminium alloy 6060 (EN 573-3) supplied in accordance with T5 (standard EN 515) and tolerances on dimensions and thicknesses according to standard UNI EN 12020.2 and/or UNI EN 755-9.

Depth of panel: 44 mm.

Closure system with black nylon handle; hinges in extruded aluminium, anodised or coated, with a galvanised steel pin.

Optional insertion of panels of a thickness ranging between 25 mm and 40 mm; insulation panels made of two sheets (unless otherwise specified) of pre-coated galvanised steel separated by high density polyurethane or polystyrene insulation material.

Fixed "U-shaped" 40/50/60 mm frame or T-/Z-/L-shaped frame to be used with or without a counter frame for any wall thickness; the T-/Z-shaped frame has been designed mainly for external fitting applications.